

Product description	<b>M12-B cable connector, Contacts: 2, shielded, moulded on cable, IP67, UL listed, PUR purple, 1 x 2 x 0.25 mm<sup>2</sup></b>
Area	<b>M12-B series 766</b>
Order number	<b>77 4329 0000 60702-0200</b>

Illustration	Scale drawing	Contact arrangement								
		<table style="margin-left: auto; margin-right: auto;"> <tr> <td>1</td> <td>n. C.</td> </tr> <tr> <td>2</td> <td>grün/green</td> </tr> <tr> <td>3</td> <td>n. C.</td> </tr> <tr> <td>4</td> <td>rot/red</td> </tr> </table>	1	n. C.	2	grün/green	3	n. C.	4	rot/red
1	n. C.									
2	grün/green									
3	n. C.									
4	rot/red									

## Technical data

### General values

Connector design	cable connector
Connector locking system	screw
Termination	moulded on cable
Wire gauge (mm)	0.25 mm <sup>2</sup>
Wire gauge (AWG)	24
Upper limit temperature	80 °C
Lower limit temperature	- 25 °C
Customs tariff number	85444290
Packaging Unit	1

### Cable data

Cable length	2 m
Sheath material	PUR
Single-lead insulation	PE-Schaum
Single-lead structure	19 x 0,127 mm
Cable diameter	7.8 mm
Approval 1	UL listed

### Electrical values

Rated current (40 °C)	4 A
Rated voltage	60 V
Rated impulse voltage	1500 V
Pollution degree	3
Overvoltage category	II
Insulating material group	II
Insulation resistance	> 10 <sup>8</sup> Ω
EMC compliance	shielded
Degree of protection	IP67
Mechanical operation	> 100 Mating cycles

### Material

Contact material	CuZn (brass)
Contact plating	Au (gold)
Contact body material	PUR
Housing material	PUR

Product description	<b>M12-B cable connector, Contacts: 2, shielded, moulded on cable, IP67, UL listed, PUR purple, 1 x 2 x 0.25 mm<sup>2</sup></b>
Area	<b>M12-B series 766</b>
Order number	<b>77 4329 0000 60702-0200</b>

## Security notices

The connector must not be connected or separated under load. Non-observance and incorrect use can result in personal injury.

The connectors are designed for use in plant, control system and electrical equipment. The end user is responsible for checking whether the connectors are suitable for use in other applications.

Connectors with degree of protection IP 67 and IP 68 are not suitable for use under water. When used outdoors, the connectors must be separately protected against corrosion. For further information about IP degrees of protection refer to 'Technical support' in the Download Centre.

To lock the cable connector to the equipment connector, the threaded ring is tightened until it is 'finger-tight' (approx. 50 cNm).